

Appl. No.: 10/669,980  
Amdt. dated 12/12/2005  
Reply to Office action of 10/20/2005

Amendments to the Claims:

1. (Currently Amended) An insulation which is resistant to ballistic impact, comprising:
  - a first layer of high-strength, ballistic resistant polymeric fabric;
  - a layer of material having a cellular structure disposed upon said first fabric layer; and,
  - a second layer of high-strength polymeric fabric disposed upon said cellular material, andwherein at least one of the layers of high-strength polymeric fabric comprises a honeycomb cross-section.
2. (Original) The insulation of Claim 1, wherein the cellular material is selected from the group consisting of close-celled polymer foams, open-celled polymer foams, open-celled aerogels, and open-celled graphitic foams.
3. (Original) The insulation of Claim 2, wherein the layer of cellular material at least partially infiltrates the fabric layers.
4. (Original) The insulation of Claim 3, further comprising a matrix of cellular material surrounding said first and second fabric layers.
5. (Original) The insulation of Claim 1, wherein the fabric layers comprise one or more plies of woven polymer fabric.
6. (Original) The insulation of Claim 5, wherein the first fabric layer is woven of fibers selected from the group consisting of aramids, polyethylenes, and polybenzazoles, and interwoven combinations thereof.
7. (Original) The insulation of Claim 6, wherein the first fabric layer is capable of absorbing up to about 30,000 ft-lbs of kinetic energy without rupture.
8. (Original) The insulation of Claim 5, wherein the second fabric layer is woven of fibers selected from the group consisting of aramids, polyethylenes, and polybenzazoles, and interwoven combinations thereof.

Appl. No.: 10/669,980  
Amdt. dated 12/12/2005  
Reply to Office action of 10/20/2005

9. (Original) The insulation of Claim 8, wherein the second fabric layer is capable of absorbing up to about 30,000 ft-lbs of kinetic energy without rupture.

10. (Original) The insulation of Claim 1, further comprising at least one thermal insulation layer wherein the thermal insulation layer comprises a fabric layer having thermal resistance.

11. (Original) The insulation of Claim 10, wherein the thermal insulation layer is a glass fabric layer.

12. (Original) The insulation of Claim 1, further comprising a radiation control layer formed of a thin film selected from the group consisting of a thin metal film and an aluminized polyester film.

13. (Currently Amended) The insulation of Claim 1, wherein the relative positioning of the layers and the particular compositions of the ballistic resistant layer and the cellular material is determined by the desired end use of the resulting insulation.

14. (Original) The insulation of Claim 1, wherein the insulation is resistant to penetration by a fragment having a kinetic energy greater than about 1700 ft-lbs.

15. (Original) The insulation of Claim 14, wherein the insulation is resistant to penetration by a fragment having a kinetic energy greater than about 3500 ft-lbs.

16. (Currently Amended) An insulated system comprising  
a container for retaining at least one fluid; and  
an insulation blanket disposed upon at least a portion of said container, said insulation blanket comprising  
a first layer of high-strength, ballistic resistant polymeric fabric;  
a layer of material having a cellular structure disposed upon said first fabric layer;  
and,

Appl. No.: 10/669,980  
Amdt. dated 12/12/2005  
Reply to Office action of 10/20/2005

a second layer of high-strength polymeric fabric disposed upon said cellular material, and wherein at least one of the layers of high-strength polymeric fabric comprises a honeycomb cross-section.

17. (Original) The insulated system of Claim 16, wherein the container is selected from the group consisting of a fuel tank, a fuel transfer line, a hydraulic tank, and a hydraulic transfer line.
18. (Original) The system of Claim 16, wherein the container is a hydrazine fuel tank.
19. (Original) The system of Claim 16, wherein the container is incorporated into the fuel system of a vehicle.
20. (Original) The system of Claim 16, wherein the container is incorporated into the hydraulic system of a vehicle.
21. (Original) The system of Claim 16, wherein the insulation is resistant to penetration by a fragment having a kinetic energy greater than about 1700 ft-lbs.
22. (Original) The system of Claim 21, wherein the insulation is resistant to penetration by a fragment having a kinetic energy greater than about 3500 ft-lbs.
23. (Currently Amended) An insulated hydrazine fuel tank comprising  
a container for retaining hydrazine fuel; and  
an insulation blanket disposed upon at least a portion of said container, said insulation blanket comprising  
a first layer of high-strength, ballistic resistant polymeric fabric;  
a layer of material having a cellular structure disposed upon said first fabric layer;  
and,

Appl. No.: 10/669,980  
Amdt. dated 12/12/2005  
Reply to Office action of 10/20/2005

a second layer of high-strength polymeric fabric disposed upon said cellular material, and wherein at least one of the layers of high-strength polymeric fabric comprises a honeycomb cross-section.

24. (Previously Presented) The system of Claim 16, wherein the layer of cellular material at least partially infiltrates the fabric layers.

25. (Previously Presented) The fuel tank of Claim 23, wherein the layer of cellular material at least partially infiltrates the fabric layers.